



F81-A0204-P4

Features

- H.264 and H.265 video streams
- 4K, 5MP, 4MP, 3MP, 2MP, 1.3MP, 1MP recording resolution
- 4ch 4MP real time live view, 4ch 8MP realtime recording, 4ch 4MP real time Playback
- Multiple selectable recording modes (continuous, motion detection and event)
- ONVIF Version 2.3 conformance
- 4 independent 48V PoE network ports
- Supports 2*HDD, each up to 8TB
- Front panel control
- VGA and HDMI video outputs
- 4ch alarm input, and 1ch alarm output
- 1-ch Audio Output(RCA)
- Operating Temperature: 14°~131°F/-10°~ 55°C
- CE, FCC, RoHS
- Comes with a 15-months warranty
- Web client support Internet Explorer, Firefox, Chrome, Safari
- PC Client support Win7 and Win8 and MAC
- Free mobile app for remote viewing of live and recorded video (iOS and Android)
- Infilux P2P enabled.
- Power supply built in the chassie
- 1 USB2.0 and 1 USB 3.0 ports, E-SATA
- Provide IE Activex, CMS, StreamView APP
- Max Bandwidth: 50Mbps

Ordering information

F81-A0204-P4

4ch network camera video access,
2 SATA HDDs, each HDD up to 8TB, no
Hard disks, 1 HDMI (up to 4K), 1 VGA,
4ch alarm in, 1ch alarm out,
4 PoE ports,
DC 48V

F81-A0204-P4-2T

4ch network camera video access, with
Hard disks, Supports 2TB of total
storage capacity

F81-A0204-P4-4T

4ch network camera video access, with
Hard disks, Supports 4TB of total
storage capacity

F81-A0204-P4-8T

4ch network camera video access, with
Hard disks, Supports 8TB of total
storage capacity

Technical specifications

Model	F81-A0204-P4
Recording Bandwidth	Max 50Mbps
Recording Resolution	8MP(4K), 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)
Display Split	1/4
Live/Playback Performance	4K: 1ch realtime 4MP/3MP/2MP: 4ch realtime
Output Interface	1 HDMI (up to 4K), 1 VGA
Display Resolution	1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 1680*1050, 1600*1200, 1900*1200, 2560*1440, 3840*2160
Alarm Input/Out	4ch in / 1ch out
Ethernet	RJ-45 port (1000M)
Smart Phone	iOS, Android
Internal HDD	2 SATA HDDs, each HDD up to 8TB
RS485	yes
e-Sata	yes
Line In	yes
USB	1x3.0 USB for backup/upgrade, 2x 2.0 USB for mouse
ONVIF	ONVIF Version 2.3 conformance
POE	4 PoE ports
Power Supply	DC48V, PoE Swith: 48V
Dimension (W×D×H)	380*340*50mm